


PLUGS



SOCKETS



Industrial Interchange

Manual

Automatic Complies With A-A-59439

Safety

Female Thread

1/4 FPT

3/8 FPT 53-5

1/2 FPT 55-5

3/4 FPT 57-5

Male Thread

1/4 MPT 50-5

3/8 MPT 52-5

1/2 MPT 54-5  $\Delta$  ■

3/4 MPT 56-5

Hose Stem (Require Hose Clamps)

1/4 I.D.

3/8 I.D. 59-5

1/2 I.D. 60-5 ■

3/4 I.D. 61-5

Push-On Hose Stem

3/8 I.D. 71-5

1/2 I.D. 81-5

Self-Storing Air Hose

1/2 I.D. 8-5

Reusable Hose Clamp

ID X OD

1/4 X 1/2 PB3-5

1/4 X 9/16 PB5-5

1/4 X 5/8 PB7-5

1/4 X 11/16 PB9-5

3/8 X 5/8 PD7-5

3/8 X 11/16 PD9-5

3/8 X 3/4 PD11-5

3/8 X 13/16 PD13-5

1/2 X 13/16 PP13-5

1/2 X 7/8 PP15-5

1/2 X 15/16 PP17-5

1/2 X 1 PP19-5

BALL CHECK

1/2 MPT

54-5G ■

1/2 I.D. Hose

60-5G

SWIVEL (Free Swivel Under Pressure)

1/2 MPT

54S-5

4015		FM4015		SV5005	
5005		FM5005		SV5205 $\Delta$	
5205		FM5205		SV5405	
5405		FM5405			
4905		FM4905			
5105		FM5105		SV5105	
5305		FM5305		SV5305 $\Delta$	
5505		FM5505		SV5505 $\Delta$	
5605		FM5605			
5705		FM5705		SV5705	
5805		FM5805		SV5805	
5905		FM5905		SV5905	
1815		FM1815			
1805		FM1805			
SD7-5		FMSD7-5			
SD9-5		FMSD9-5			
SD11-5		FMSD11-5			
SD13-5		FMSD13-5			
SP13-5		FMSP13-5			
SP15-5		FMSP15-5			
SP17-5		FMSP17-5			
SP19-5		FMSP19-5			



CO-AXIAL COUPLERS



Safety sockets and plugs marked  $\Delta$  above are available with co-axial tube for use on single point injection lubrication systems. Suffix CA to catalog No.