



COLOUR

- Metal grey

TEMPERATURE RANGE

- From -10°C to 60°C

FEATURES

- PVC hose reinforced with an anti-shock rigid Pvc spiral. Inside surface smooth, light corrugation outside. Its extreme strength makes it suitable for heavy-duty applications. Resistant to crushing, abrasion atmospheric agent and most chemicals

APPLICATIONS

- For suction and discharge of waters, sewage, mud, wood mixing, acid, latex, grains and other materials. It is placed on tank trucks, ships, silos, etc

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Weight g/m	Working Pressure bar	Bursting Pressure bar	Vacuum mH2O	Bending Radius mm	Roll Length mm	Volume m ³
50	5.2	5.6	1200	7.0	21	10	300	50	0.329
50.8	5.2	5.6	1220	7.0	21	10	300	50	0.334
60	5.7	6.2	1600	6.0	18	10	370	50	0.489
76.2	5.9	6.3	2000	4.5	13.5	10	470	50	0.677
100	7.3	8.1	3300	4.0	12	9	600	30	0.785
102	7.3	8.1	3350	4.0	12	9	600	30	0.798
127	7.5	8.3	4200	3.5	10.5	9	750	30	1.245
152.8	9.2	10.2	6300	3.0	9	9	900	20	1.359
200	11.0	12.2	10000	2.0	6	7	1200	10	2.172

Can be manufactured antistatic upon request