



COLOR

- Opaque translucent

WORKING TEMPERATURE

- From -40°C to 50°C (-40F to 122F)

FEATURES

- Clear thermoplastic compound with rubber features. Zinc plated steel wire. Extremely flexible even at very low temperature. This hose is PVC, halogens, phtalates and metals free. Water and microbes resistant does not stick on surface. Food grade* in conformity to CE Regulations

APPLICATIONS

- Suction and blow of air, gas, powders, dust, flour and of light duty abrasives. Can be used in ventilation, woodworking and in various applications in the food industry

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Weight g/m	Vacuum mH2O	Bending Radius mm	Roll Length* mm	Volume m ³
60	0.35	230	0.40	30	10	0.008
70	0.35	310	0.40	35	10	0.011
76	0.35	335	0.40	38	10	0.012
80	0.35	355	0.40	40	10	0.014
90	0.35	390	0.40	45	10	0.018
100	0.40	440	0.30	50	10	0.024
110	0.40	480	0.30	55	10	0.029
120	0.40	525	0.25	60	10	0.034
127	0.40	550	0.25	64	10	0.038
130	0.40	570	0.20	65	10	0.040
140	0.40	610	0.20	70	10	0.046
150	0.40	655	0.20	75	10	0.052
160	0.45	770	0.15	80	10	0.067
180	0.45	860	0.15	90	10	0.083
200	0.45	955	0.10	100	10	0.101
250	0.50	1120	0.10	125	10	0.156
300	0.50	1335	0.08	150	10	0.220
350	0.50	1570	0.07	175	10	0.296
400	0.50	1790	0.06	200	10	0.383

* Please contact our offices for more information