


COLOUR

- Black with green stripe

TEMPERATURE RANGE

- From -40°C to 125°C

FEATURES

- Flexible duct made in thermoplastic rubber with a steel spiral reinforcement embedded between the two layers. Light and flexible is extremely resistant to high temperatures, chemicals and abrasion

APPLICATIONS

- Suction of hot air and fumes in chemical plants and shipyards

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Vacuum mH2O	Bending Radius mm	Roll Length mm	Volume m ³
38	0.4	190	2.0	30	20	0.074
40	0.4	200	2.0	32	20	0.077
45	0.4	230	2.0	36	20	0.092
51	0.4	250	2.0	40	20	0.108
60	0.4	300	1.7	50	20	0.137
63	0.4	310	1.7	55	20	0.150
70	0.5	440	1.7	60	20	0.181
76	0.5	470	1.7	65	20	0.232
80	0.5	500	1.6	65	20	0.254
90	0.5	580	1.6	75	20	0.294
102	0.6	620	1.3	85	15	0.286
110	0.6	660	1.2	90	15	0.318
120	0.6	730	1.0	100	15	0.369
127	0.65	840	1.0	105	15	0.405
130	0.65	870	0.8	105	15	0.427
140	0.65	950	0.8	115	15	0.504
152	0.65	1030	0.8	125	15	0.544
160	0.65	1100	0.7	130	15	0.666
180	0.65	1350	0.5	150	15	0.864
203	0.65	1500	0.4	165	15	1.157
228	0.65	1700	0.4	185	10	0.941
254	0.65	1950	0.4	210	10	1.197
279	0.65	2150	0.4	230	10	1.426
305	0.65	2400	0.3	250	10	1.633
356	0.65	2790	0.3	300	-	-
406	0.65	3250	0.3	350	-	-