



COLOUR

- Translucent with coppered steel wire

WORKING TEMPERATURE

- From -20°C to 80°C (-4F to 176F)

FEATURES

- Hose in a special vinyl and ester based PU compound. Designed on purpose for the woodworking industry. Coppered steel wire reinforcement. Wall thickness from 0,90 till 1,30 mm. Flame resistant according to UL 94 V0, meets the safety standards of the German Wood Trade Association. High flexibility and abrasion resistance.

APPLICATIONS

- Suction of saw shavings and sawdust, in sawmills and woodworking plants

Meets the RoHS Norms

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Weight g/m	Vacuum mH2O	Bending Radius mm	Roll Lenght mm	Volume m ³
40	0.90	430	5.0	50	20	0.079
45	0.90	480	5.0	50	20	0.092
51	0.90	510	5.0	60	20	0.108
60	0.90	595	4.0	70	20	0.137
63	0.90	625	4.0	70	20	0.152
65	0.90	645	4.0	70	20	0.164
70	1.10	765	4.0	80	20	0.184
76	1.10	770	3.5	90	20	0.235
80	1.10	810	3.5	90	20	0.256
90	1.10	890	3.0	100	20	0.297
100	1.10	965	2.5	120	15	0.283
110	1.10	1260	2.5	130	15	0.323
120	1.10	1360	2.0	140	15	0.374
127	1.10	1405	2.0	150	15	0.408
130	1.10	1450	2.0	150	15	0.431
140	1.10	1555	1.5	160	15	0.507
150	1.10	1640	1.5	170	15	0.541
160	1.30	2255	1.5	180	15	0.670
180	1.30	2565	1.0	210	15	0.860
200	1.30	2795	1.0	230	15	1.135
220	1.30	3105	0.5	250	10	0.906
228	1.30	3215	0.5	260	10	0.937
250	1.30	3510	0.5	290	10	1.179
279	1.30	3945	0.5	320	10	1.416
300	1.30	4220	0.5	350	10	1.597