



COLOUR

- Transparent with ivory spiral

TEMPERATURE RANGE

- From -20°C to 80°C (-4F to 176F)

FEATURES

- Ether based PU wall , food grade, with antishock rigid PVC spiral. Smooth inside, corrugated outside. Light, extremely resistant to abrasion and flexion, this hose features high mechanical properties. Resistant to many chemicals

APPLICATIONS

- Light suction of dry food according to EC Directives and regulations*

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Weight g/m	Vacuum mH2O	Bending Radius mm	Roll Length mm	Volume m ³
20	0.4	2.6	110	2.5	25	20	0.028
25	0.4	2.6	150	2.5	30	20	0.035
30	0.4	2.6	160	2.5	35	20	0.049
31.8	0.4	2.6	180	2	35	20	0.051
35	0.5	2.7	200	2	45	20	0.059
38.1	0.5	2.8	220	2	50	20	0.068
40	0.5	2.8	230	2	60	20	0.071
45	0.5	2.9	270	2	65	20	0.083
50.8	0.5	3.2	320	2	70	20	0.104
55	0.5	3.4	400	2	75	20	0.119
60	0.5	3.6	470	1.6	80	20	0.170
63.5	0.5	3.6	510	1.6	80	20	0.180
65	0.5	3.6	520	1.6	90	20	0.191
70	0.6	3.9	560	1.6	95	30	0.293
76.2	0.6	3.9	600	1.6	100	30	0.328
80	0.6	4.2	650	1.6	110	30	0.357
90	0.6	4.3	750	1.4	125	30	0.547
100	0.6	4.4	820	1.3	140	30	0.640
102	0.6	4.4	830	1.3	140	30	0.652
110	0.6	4.7	950	1.2	150	30	0.743
120	0.6	5.0	1100	1	160	30	0.831
127	0.6	5.0	1150	1	170	30	0.900
130	0.7	5.3	1300	0.9	170	20	0.780
140	0.7	5.3	1430	0.9	180	20	0.860
151.5	0.7	5.3	1500	0.8	200	20	0.953
152.8	0.7	5.3	1520	0.8	200	20	0.961
160	0.7	6.7	1940	0.7	220	20	1.049
170	0.7	6.7	2030	0.5	230	20	1.140
180	0.7	6.7	2140	0.4	250	20	1.236
200	0.7	6.7	2300	0.4	260	20	1.440
203	0.7	6.7	2320	0.4	260	20	1.460
250	0.8	7.5	3400	0.4	300	10	0.952
300	0.8	7.7	4100	0.3	350	10	