



COLORE

- Transparent with ivory spiral

TEMPERATURE RANGE

- From -20°C to 80°C (-4F to 176F)

FEATURES

- Ether based PU wall ,food grade, with antishock rigid PVC spiral. Smooth inside, corrugated outside. Light, flexible, extremely resistant to abrasion and flexion, this hose features high mechanical properties. Resistant to many chemicals.

APPLICATIONS

- Medium suction of dry food such as grains, animal feed, sugar, flour according to EC Directives and regulations*

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Weight g/m	Vacuum mH2O	Bending Radius mm	Roll Length mm	Volume m ³
30	0.8	3.0	250	3.5	100	30	0.083
35	0.8	3.3	290	3	120	30	0.101
38.1	0.8	3.3	310	3	130	30	0.114
40	1.0	3.6	350	3	140	30	0.133
45	1.0	4.0	440	3	160	30	0.150
50.8	1.0	4.5	550	3	175	30	0.201
60	1.0	4.5	640	3	200	30	0.241
63.5	1.0	4.5	670	3	230	30	0.293
70	1.0	4.5	750	3	250	30	0.369
76.2	1.0	4.5	780	2.5	270	30	0.432
80	1.0	5.0	900	2.5	290	30	0.485
90	1.0	5.2	1050	2.5	360	30	0.573
100	1.0	5.7	1250	2.5	400	30	0.713
102	1.0	5.7	1270	2.5	400	30	0.725
110	1.0	5.8	1400	2.5	440	30	0.842
120	1.0	5.9	1500	2.5	470	30	0.962
127	1.0	5.9	1600	2.5	500	30	1.120
130	1.0	5.9	1650	2.5	520	30	1.145
140	1.0	6.0	1800	2	570	30	1.646
151.5	1.0	6.4	2000	2	600	20	1.262
203.2	1.2	8.9	2900	1	400	20	1.768
254	1.2	8.9	3600	1	500	10	2.175
304.8	1.2	8.9	4300	0.8	610	10	2.581

* Please contact our offices for more information
On request is available also in the antistatic version