


COLOUR

- Orange

TEMPERATURE RANGE

- From -25°C to 50°C

FEATURES

- Plasticized PVC duct with rigid antishock PVC spiral. Inside smooth, outside corrugated. Flexible particularly at low temperatures, high mechanical resistance. Resists to atmospherical agents and to most chemicals

APPLICATIONS

- When a vacuum resistant flexible hose is needed, for industry, domestic vacuum cleaners, aerating and conditioning plants and suction of fumes, gasses, etc

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Weight g/m	Vacuum mH2O	Bending Radius mm	Roll Length mm	Volume m ³
25	1.2	2.6	175	6	80	50	0.072
31.8	1.4	3.1	280	6	110	50	0.110
38.1	1.5	3.2	350	5	130	50	0.165
40	1.5	3.2	370	5	140	50	0.180
45*	1.6	3.4	450	5	160	50	0.210
50	1.6	3.9	550	5	175	50	0.266
50.8	1.	3.9	560	5	175	50	0.270
60*	2.0	4.6	850	5	200	50	0.372
63.5	2.0	4.6	905	5	220	50	0.405
76.2	2.0	5.2	1100	5	270	50	0.641
80*	2.0	5.4	1200	5	290	50	0.672
90*	2,0	5.4	1300	5	350	30	0.593
102	2.1	5.6	1530	4.5	400	30	0.724
127*	2.2	6.5	2200	4.5	500	30	0.996
151.5*	2.5	7.3	3000	4	600	20	0.977
200*	2.7	8.0	4100	3.5	800	20	1.577