



COLOUR

- Grey

TEMPERATURE RANGE

- From -20°C to 100°C (peaks 120°C)

FEATURES

- Flexible duct made in flame resistant PVC coated polyester fabric and reinforced by steel helix welded between the two layers. Axial compressibility: 8:1

APPLICATIONS

- Civil and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders, gas

Technical Data

Inside Ø mm	Weight g/m	Bending Radius mm	Roll Length mm	Volume m ³
40	110	20	10	0.002
51	135	26	10	0.003
60	160	30	10	0.004
63	170	32	10	0.005
70	185	35	10	0.006
76	200	38	10	0.006
80	210	40	10	0.007
90	240	45	10	0.009
102	280	51	10	0.011
110	300	55	10	0.013
115	315	58	10	0.014
120	325	60	10	0.016
127	345	64	10	0.017
130	355	65	10	0.018
140	380	70	10	0.021
152	410	76	10	0.025
160	425	80	10	0.028
180	475	90	10	0.035
203	535	102	10	0.044
228	600	114	10	0.055
254	845	127	10	0.068
279	925	140	10	0.082
305	1010	153	10	0.098
315	1045	158	10	0.104
330	1090	165	10	0.114
356	1180	178	10	0.132
406	1340	203	10	0.171

* Antistatic version available

Flame retardant V(TM)-0 according to UL 94 and M2 grade according to NFP 92 503