



COLOUR

- Clear with ivory spiral

TEMPERATURE RANGE

- From -10°C to 60°C (14F to 140F)

FEATURES

- PVC hose reinforced by antishock rigid PVC spiral. Inside smooth, light and very flexible. Robust, resistant to fatigue, weather and most chemical products

APPLICATIONS

- Suction and delivery of alimentary products (no fatty foods) such as drinks, fruit juices, wine, vinegar and liqueurs up to a maximum alcoholic content of 15%

Meets EC Directives and regulation*

Technical Data

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Weight g/m	Working Pressure bar	Bursting Pressure bar	Vacuum mH2O	Bending Radius mm	Roll Lenght mm	Volume m ³
13	2.4	2.7	160	10.0	30	7	75	50	0.039
13	2.4	2.7	160	10.0	30	7	75	50	0.039
19.1	2.6	2.9	240	7.0	21	7	110	50	0.059
20	2.6	2.9	250	7.0	21	7	110	50	0.070
25	2.6	2.9	300	7.0	21	7	130	50	0.084
30	2.7	3.0	360	6.0	18	7	150	50	0.115
31.8	2.7	3.0	390	6.0	18	7	155	50	0.127
35	2.7	3.2	440	6.0	18	7	170	50	0.153
38.1	2.9	3.5	520	5.0	15	7	180	50	0.182
40	3.0	3.5	550	5.0	15	7	195	50	0.199
45	3.2	3.8	670	5.0	15	7	215	50	0.232
50	3.3	4.2	800	5.0	15	7	235	50	0.293
50.8	3.3	4.2	810	5.0	15	7	235	50	0.297
55	3.4	4.3	900	5.0	15	7	255	50	0.330
60	3.4	4.2	970	5.0	15	7	275	50	0.449
63.5	3.4	4.3	1040	5.0	15	7	290	50	0.487
70	3.7	4.6	1200	5.0	15	7	320	50	0.535
76	3.9	4.8	1380	5.0	15	7	340	50	0.654
80	4.2	5.2	1550	4.0	12	7	365	50	0.709
90	4.4	5.5	1850	4.0	12	7	420	30	0.577
100	4.8	6.0	2200	4.0	12	7	470	30	0.716
102	4.8	6.0	2240	4.0	12	7	470	30	0.729
110	5.0	6.3	2550	4.0	12	6	520	30	0.850
120	5.1	6.4	2800	3.0	9	6	650	30	0.969
127	5.2	6.5	3000	3.0	9	5.5	680	30	1.129
151.5	6.1	7.6	4300	3.0	9	5	780	20	1.281

* Please contact our offices for more information

The antistatic version and the low temperature (-25°C / -16°F) are available on request. PU version is also available