



**COLOUR**

- Light blue

**TEMPERATURE RANGE**

- From -10°C to 60°C (14F to 140F)

**FEATURES**

- Hose in special antimigration PVC compound reinforced with an antishock rigid PVC spiral, it's resistant to abrasion, ageing, atmospheric agents and ozone

**APPLICATIONS**

- For suction and delivery of mineral oil, lubricants, crude oils (naphta and diesel oil)

**Technical Data**

Inside Ø mm	Minimum Wall Thickness mm	Maximum Wall Thickness mm	Weight g/m	Working Pressure bar	Bursting Pressure bar	Vacuum mH2O	Bending Radius mm	Roll Lenght mm	Volume m <sup>3</sup>
19.1	4.0	4.2	400	8	24	10	140	50	0.071
20	4.0	4.2	420	8	24	10	140	50	0.074
25	4.3	4.6	550	8	24	10	170	50	0.098
30	4.4	4.6	650	8	24	10	195	50	0.138
31.8	4.4	4.7	700	8	24	10	205	50	0.145
38.1	4.4	4.7	810	7	21	10	235	50	0.193
40	4.3	4.7	830	7	21	10	250	50	0.222
45	4.4	4.8	950	6	18	10	275	50	0.264
50	4.9	5.3	1150	6	18	10	300	50	0.326
50.8	4.9	5.3	1170	6	18	10	300	50	0.330
60	5.4	5.9	1550	6	18	10	355	50	0.485
63.5	5.6	6.0	1690	6	18	10	370	50	0.511
76.2	5.8	6.3	2060	5	15	10	440	50	0.676
80	5.9	6.6	2210	5	15	10	460	30	0.548
90	6.2	6.9	2610	4	12	10	530	30	0.611
100	7.1	7.9	3310	4	12	9	600	30	0.782
102	7.1	7.9	3370	4	12	9	600	30	0.795