



**APPLICATIONS**

- Recommended as tanktruck, railcar and inplant transfer.

**TEMPERATURE**

- -30°C(-22°F) to +90°C(+194°F)

**WORKING PRESSURE**

- 150 psi

**SAFETY FACTOR**

- 5:1

**MAX. LENGTH**

- 65feet (20 meter)

**COMPLIES WITH**

- BS EN 13765: 2010

**TECHNICAL DATA**

Code	Service	Inner Wire	Tube	Colour
0804-GG	Oil/solvents	Galvanized steel	Polypropylene	Blue
0416-PG	Chemical	Polypropylene coated steel	Polypropylene	Black
0414-SG	Chemical	Stainless steel 316	Polypropylene	Green
0426-SG	Chemical	Stainless steel 316	Teflon	Red

\* Outer wire in galvanised steel, stainless steel outer wire on request.

I.D Ø		Working Pressure		Min Bend Radius		Approx. Weight	
(inch)	(mm)	(psi)	(bar)	(inch)	(mm)	(lbs/ft)	(kg/m)
1	25	150	10	4	100	0,65	1,00
1-1/4	32	150	10	4-3/4	120	0,75	1,12
1-1/2	38	150	10	5-1/4	130	0,85	1,25
2	50	150	10	6-1/2	165	1,20	1,80
2-1/2	65	150	10	7-1/2	185	1,70	2,50
3	80	150	10	9-1/2	240	2,00	3,00
4	100	150	10	14-1/2	360	3,00	4,50