



APPLICATIONS

- Recommended for heavy duty marine operations, including ship and barge loading and unloading.

TEMPERATURE

- -30°C (-22°F) to +100°C (212°F)

WORKING PRESSURE

- 150 thru 200 psi

SAFETY FACTOR

- 5:1

MAX. LENGTH

- 65feet (20 meter)

COMPLIES WITH

- BS EN 13765:2010

TECHNICAL DATA

Code	Service	Inner Wire	Tube	Colour
0824-GG	Oil/solvents	Galvanized steel	Polypropylene	Blue
0436-PG	Chemical	Polypropylene coated steel	Polypropylene	Black
0434-SG	Chemical	Stainless steel 316	Polypropylene	Green
0444-SG	Chemical	Stainless steel 316	Teflon	Red

*Outer wire in galvanised steel, stainless steel outer wire on request.

I.D Ø		Working Pressure		Min Bend Radius		Approx. Weight	
(inch)	(mm)	(psi)	(bar)	(inch)	(mm)	(lbs/ft)	(kg/m)
3	75	200	14	11	280	2,50	3,70
4	102	200	14	16	400	4,40	6,50
5	125	200	14	18	460	5,80	8,60
6	152	200	14	20	500	7,00	10,50
8	204	200	14	29	740	12,00	18,00
10	254	150	10	36	920	15,00	23,00