




VACUUM HOSE

Great for Air

DAYFLEX®

DFD-T



APPLICATIONS

Great for heater/defroster, ventilation and industrial air movements applications.

FEATURES

- Defrost hose
- Pliable helix can be formed to fit various applications
- Flexible, crush resistant and compressible
- Meets FMVSS 302 flame standards
- Can be manufactured with PVC materials on request

CONSTRUCTION

Lightweight thermoplastic propylene-ethylene copolymer reinforced with an internal polypropylene helix.

INDUSTRIES

Automotive, Brake ducting, Bus, Cab ventilation, Conduits, Defroster/Heater, Limo A/C Duct, Printing,

R.V. Manufacturing

SIZES (inch)

1" - 4"

I.D TOLERANCES (inch)

-0.02" to +0.02" (to 4")

TEMPERATURE RANGE (°F)

-40°F to 225°F

COLOURS

Black

END FINISH

Plain Cut

STANDARD LENGTH (feet)

25', 50'

I.D Ø		Min. Centerline Bend Radius		Compression Ratio	Max. Recommended (-) Press	Max. Recommended (+) Press	Approx. Weight
(inch)	(mm)	(inch)	(mm)	(x:1)	(in./hg)	(psi)	(lbs/ft)
1	N/A	1	25.4	2:1	N/A	11	0.04
1.25	N/A	1.5	38.1	2:1	N/A	10	0.06
1.5	N/A	2	50.8	3:1	N/A	10	0.08
1.75	N/A	2.5	63.5	3:1	N/A	10	0.09
2	N/A	3	76.2	3:1	N/A	10	0.10
2.25	N/A	3.5	88.9	3:1	N/A	9	0.11
2.5	N/A	3.75	95.3	3:1	N/A	9	0.13
3	N/A	4.25	108.0	3:1	N/A	8	0.14
4	N/A	4.5	114.3	3:1	N/A	3	0.22

Note: Technical data based on 2 ft. straight lengths of hose @ 72° F.

No applicable end fittings and connectors available for this model.

The proper use and maintenance of hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability.

