



ALL PLASTIC , WET/DRY VACUUM HOSE

Great for Material

GENESIS®

DPZ



APPLICATIONS

Ideal for light bulk material handling applications.

FEATURES

- Smooth interior assures efficient air flow
- Light weight & flexible even at low temperatures
- Superior external abrasion resistance
- Ideal for wet/dry vacuum in car wash, commercial & industrial applications
- Very good chemical resistance
- Crush resistant
- Cuffs & custom colors available**

CONSTRUCTION

Light weight gray polyethylene copolymer hose reinforced with an integral polyethylene helix.

INDUSTRIES

Bus Ventilation, Car Wash, Pet Grooming Equipment, Pipe Organs, Residential Vacuum Cleaners

SIZES (inch)

1-1/4" - 2"

TEMPERATURE RANGE (°F)

-40°F to 140°F

COLOURS

Grey

STANDARD LENGTH (feet)

25', 50'

END FINISH

Plain cut

I.D Ø	Wall Thickness	Min. Centerline Bend Radius		Compression Ratio	Max. Recommended (-) Press	Max. Recommended (+) Press	Approx. Weight
(inch)	(inch)	(inch)	(mm)	(x:1)	(in./hg)	(psi)	(lbs/ft)
1.25	N/A	2.50	63.5	N/A	29	20	0.160
1.5	N/A	3.00	76.2	N/A	29	18	0.200
2	N/A	3.50	88.9	N/A	29	15	0.260

Note: Technical data based on 2 ft. straight lengths of hose @ 72° F.

**Consult sales team on pricing & minimums

AVAILABLE END FITTINGS AND CONNECTORS



Connector Cuffs

Threads on end.

Sizes: 1-1/4", 1-1/2", 2"

Colours: Grey

Polyweld Cuffs

Permanently welded to the end of the hose to provide an air tight seal.

Sizes: 1-1/4", 1-1/2", 2", 2-1/2"

Colours: White

Screw Cuffs

Threads on end

Sizes: 1-1/4", 1-1/2", 2", 2 1/2", 3", 4"

Colours: Grey

The proper use and maintenance of hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability.

