



APPLICATIONS

Ideal for low pressure air movement and fume extraction applications.

FEATURES

- Suited for low pressure air movement & fume extraction
- Excellent for light vacuum applications
- Light weight & very flexible
- Economical choice for woodworking & dust collection applications
- Moderate abrasion resistance
- Crush resistant

CONSTRUCTION

Light weight black polyethylene hose reinforced with an integral polyethylene helix.

INDUSTRIES

A/C Ventilation, Bilge Pumping, Bus Ventilation, Cab Ventilation, Circuit Board Cooling, Electronic Panel Cooling, Limo A/C Duct, Pipe Organs, Stereo Speakers

SIZES (inch)

2" - 4"

TEMPERATURE RANGE (°F)

-40°F to 140°F

COLOURS

Black

STANDARD LENGTH (feet)

25', 50'

END FINISH

Plain cut

I.D Ø	Wall Thickness	Min. Centerline Bend Radius		Compression Ratio	Max. Recommended (-) Press	Max. Recommended (+) Press	Approx. Weight
		(inch)	(mm)				
2	N/A	2.50	63.5	N/A	29	19	0.180
2.5	N/A	3.00	76.2	N/A	16	11	0.220
3	N/A	4.00	101.6	N/A	10	11	0.270
4	N/A	7.00	177.8	N/A	8	10	0.360

Note: Technical data based on 2 ft. straight lengths of hose @ 72° F.
No applicable end fittings and connectors available for this model.