



VACUUM HOSE

Great for Material

DAYFLEX®

SANIFLEX®



APPLICATIONS

Ideal for light bulk material handling and as a potable water hose in RV applications.

FEATURES

- Potable water hose
- Very smooth inner surface assures minimal friction loss and efficient air flow
- Lightweight and flexible
- Can also be compounded in polyurethane and thermoplastic rubber elastomer materials
- Meets IAPMO compliance

CONSTRUCTION

Plastic helix supported PVC tape hose.

INDUSTRIES

Food Grade, Meat Packing, R.V. Manufacturing, Safety Equipment

SIZES (inch)

3/4" - 2"

I.D TOLERANCES (inch)

-0.02" to +0.02" (to 2")

TEMPERATURE RANGE (°F)

-20°F to 180°F

COLOURS

Natural

END FINISH

Plain Cut

STANDARD LENGTH (feet)

50'

I.D Ø		Min. Centerline Bend Radius		Compression Ratio	Max. Recommended (-) Press	Max. Recommended (+) Press	Approx. Weight
(inch)	(mm)	(inch)	(mm)	(x:1)	(in./hg)	(psi)	(lbs/ft)
0.75	N/A	0.75	19.1	1.5:1	29	30	0.07
1	N/A	1	25.4	1.5:1	29	30	0.09
1.25	N/A	1.25	31.8	2:1	29	28	0.13
1.375	N/A	1.4	35.6	2:1	20	28	0.14
1.5	N/A	1.75	44.5	2:1	20	20	0.16
1.625	N/A	2	50.8	2:1	20	20	0.18
2	N/A	2	50.8	2:1	10	18	0.23

Note: Technical data based on 2 ft. straight lengths of hose @ 72° F.
No applicable end fittings and connectors available for this model.

The proper use and maintenance of hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability.

